

Citrix XenApp Clients Feature Overview

| | Win32 11.x | CE WBT 10.x | CE HPC 10.x | Java 9.x | Mac OS X 10.00 | Linux x86 11.x | Solaris SPARC + x86 8.x | HP-UX 6.30 | AIX 6.30 | SGI 6.00 | OS/2 6.01 | Symbian Series 60 3rd Edition 4.0 | Symbian FOMA 4.0 | Symbian Series 80 4.0 |
|--|---------------|----------------|----------------|-------------|-------------------|-------------------|----------------------------------|---------------|-------------|-------------|--------------|--|------------------------|-----------------------------|
| Display + Graphics | | | | | | | | | | | | | | |
| Core Functionality* | x | x | x | x | x | x | x | x | x | x | x | x** | x** | x** |
| Seamless Windows | x | x | | x | xx | x | x | x | x | x | | | | |
| SpeedScreen Latency Reduction | x | x | x | x | x | x | x | x | x | x | | | | |
| Panning | x | | x | x | x | x | x | x | x | x | | x | x | x |
| Scaling | x | | x | | | | | | | | | x | x | x |
| SpeedScreen Browser Acceleration | x | x | x | x | x | x | x | | | | | | | |
| SpeedScreen Multimedia Acceleration | x | x | | | | xx | | | | | | | | |
| SpeedScreen Image Acceleration | x | x | x | x | xx | x | x | | | | | | | |
| SpeedScreen Flash Acceleration (server feature and independent of client) | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| ClearType Remoting (server feature and independent of client) | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| Dynamic Session Resizing | x | x | x | x | | x | xx | | | | | | | |
| Client Device Mapping | | | | | | | | | | | | | | |
| Drives | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| Printers | x | x | x | x | x | x | x | x | x | x | x | | | |
| COM ports | x | x | x | | x | x | x | x | x | | x | | | |
| Audio (server to client) | x | x | x | x | x | x | x | x | x | | x | | | x |
| Audio (client to server) | x | x | x | | | x | x | | | | | | | |
| Clipboard | x | x | x | text only | x | x | x | x | x | x | text only | x | x | x |
| USB PDA Sync | x | § | § | | | x | | | | | | | | |
| TWAIN Support | x | § | § | | | | | | | | | | | |
| Connectivity | | | | | | | | | | | | | | |
| PN Agent Interface | x | x | x | n/a | | x | x | | | | | | | |
| Multi-Farm Support | x | x | x | n/a | | x | xx | | | | | | | |
| Password expiration support | x | | | n/a | | | | | | | | | | |
| Roaming Smart Card Support | x | | | | | | | | | | | | | |
| Backup URL | x | xx | xx | | | x | | | | | | | | |
| Support through Access Gateway | x | | | | | | | | | | | | | |
| Auto Client Reconnect | x | x | x | x | x | x | x | x | x | | | | | |
| Roaming User Reconnect | x | x | x | x | | x | x | x | x | | | | | |
| Extended Parameter Passing | x | x | x | x | x | x | x | x | x | | | | | |
| Content Publishing | x | x | x | x | | x | x | | | | | | | |
| Content Redir. Client-Svr | PN Agent | x | x | | manual | manual | manual | manual | manual | | | | | |
| Content Redir. Svr-Client | x | x | x | x | | x | x | x | x | | | | | |
| Auto Printer Detection | x | x | x | x | x | x | x | x | x | | x | | | |
| Universal Printing | x | | | x | x(v2) | x | x | | | | | | | |
| UPD v3 | x | § | § | | n/a | n/a | | | | | | | | |
| Windows Key Passthrough | x | x | | | xx | x | | | | | | | | |
| Workspace Control | x | x | x | | | x | xx | | | | | | | |
| Session Reliability | x | x | x | xx | xx | | | | | | | | | |
| Security/Authentication | | | | | | | | | | | | | | |
| Smart Card | x | x | xx | | x | x | x | | x | | | | | |
| NDS Credentials | x | x | x | x | x | x | x | x | x | | | | | |
| SSL (incl DNS resolution) | x | x | x | xx | x | x | x | x | x | | | x | x | x |
| TLS | x | x | x | x | x | x | x | x | x | | | x | x | x |
| AES Support | x | | | xx | | x | | | | | | | | |
| SOCKS 4 and 5 support | x | x | x | x | x | x | x | x | x | x | | | | |
| Auto Proxy Discovery | x | xx | xx | x | x | x | x | x | x | | | | | |
| Secure Proxy | x | x | x | x | x | x | x | x | x | | | | | |
| NTLM Proxy Authentication | x | x | x | xx | | x | | | | | | | | |
| Passthru Authentication | x | | | xx | xx | | | | | | | | | |
| Signed packages | x | | | x | | | | | | | | | | |
| Enhanced Proxy Detection | x | § | § | | | x | | | | | | | | |
| Non-administrator Client Installation | x | n/a | n/a | | | x | | | | | | | | |
| Trusted Server Configuration | x | xx | xx | | | x | | | | | | | | |
| International | | | | | | | | | | | | | | |
| Time Zone support | x | x | x | xx**** | x | x | x | x | x | | | | | |
| Enh Unicode Keyboard Support*** | x | | x | x | | x | xx | | | | | x | x | x |
| Virtual Channel SDK | | | | | | | | | | | | | | |
| | x | x | x | x | | x | xx (SPARC only) | x | x | | | | | |

* Core Functionality 1280x1024 resolution, 24 bit color depth, Memory and Persistent Cache, International keyboard support, TCP/HTTP Browsing, Disconnect/Reconnect, up to 128-bit Encryption

** The FOMA & Series 80 clients support a maximum of 256 colors, and do not support Persistent Caching

*** Enhanced Unicode Keyboard Support provides more versatile double byte character entry using the local IME and/or handwriting recognition functions

**** some limitations (details in readme)

§ Not implemented due to platform restrictions

xx = denotes change from previous version